

# 食品级双层钢丝夹布硅胶软管

Food grade double-layer steel wire sandwich silicone hose

# FP32

## 材质结构:

内/外层: 食品级铂金硅胶

增强层: 双层螺旋不锈钢丝 (钢丝间距为4MM) + 五层网状聚酯纤维编织布  
具有3倍之普通钢管的压力

## Material structure:

Inner / outer layer: Food grade platinum silica gel

Reinforcing layer: Double layer spiral stainless steel wire (steel wire spacing is 4mm) + Five layer reticulated polyester woven cloth, It has 3 times the pressure of ordinary steel pipe

## 尺寸规格:

内径: Ø13mm---159mm (支持定制)

标准长度: 6M/10M

工作温度范围: -60°C / +180°C

## Dimensions:

Internal diameter: Ø13mm---159mm(Support customization)

Standard length: 6M/10M

Length operating temperature range: -60°C / +180°C

## 产品应用:

推荐用于输送高低温食品、化妆品、化工、制药行业和生物工程用的液体或半液体等流体。如抽吸食品类乳制品; 食品机械设备用连接管; 酒类用连接导管; 油类设备抽吸用的连接管, 医药设备连接管路、导管等

## Product application:

It is recommended to transport liquid or semi liquid and other fluids used in high and low temperature food, cosmetics, chemical industry, pharmaceutical industry and bioengineering. Such as sucking food dairy products; Connecting pipe for food machinery and equipment; Connecting conduit for alcohol; Connecting pipe for oil equipment suction, connecting pipeline and conduit of medical equipment, etc

chemical industry, pharmaceutical industry and bioengineering. Such as sucking food dairy products; Connecting pipe for food machinery and equipment; Connecting conduit for alcohol; Connecting pipe for oil equipment suction, connecting pipeline and conduit of medical equipment, etc

## Food Grade Silicone Hose



外观:  
内外壁光滑  
smooth inner and outer walls

## 产品特点优势



品名 PART NAME	内径 INNER DIA		壁厚 WALL THICKNESS <sup>+1.0</sup> / <sub>-0.5</sub> mm	外径 OUTER DIA		折弯半径 BEND RADIUS (mm)	工作压力 WORK PRESSURE		爆破压力 BURST PRESSURE		标准长度 STANDARD LENGTH 米/根 M/Roll
	(mm)	(inch)		(mm)	(inch)		Bar	psi	Bar	psi	
FP32-019	19	3/4	6.5	32.0	1.3	72	27.9	404.55	83.7	1213.65	6或10
FP32-022	22	7/8	6.5	35.0	1.4	85	26.0	377	78.0	1131	6或10
FP32-025	25	1	6.5	38.0	1.5	90	24.1	349.45	72.3	1048.35	6或10
FP32-032	32	1-1/4	6.5	35.0	1.4	115	21.7	314.65	65.1	943.95	6或10
FP32-038	38	1-1/2	6.5	51.0	2	129	19.2	278.4	57.6	835.2	6或10
FP32-045	45	1-3/4	6.5	58.0	2.3	140	17.5	253.75	52.5	761.25	6或10
FP32-051	51	2	6.5	64.0	2.5	190	15.7	227.65	47.1	682.95	6或10
FP32-057	57	2-1/4	6.5	70.0	2.8	220	14.2	205.9	42.6	617.7	6或10
FP32-063	63	2-1/2	6.5	76.0	3	280	13.2	191.4	39.6	574.2	6或10
FP32-076	76	3	6.5	89.0	3.5	334	10.5	152.25	31.5	456.75	6或10
FP32-090	90	3-1/2	6.5	103.0	4.1	389	9.3	134.85	27.9	404.55	6
FP32-102	102	4	6.5	115.0	4.5	452	7.7	111.65	23.1	334.95	6

## 适用流体类型

