



风电硅胶管 SP60

Wind power silicone tube SP60



材料结构:

内外管: 蓝色工业级硅胶, 表面布纹, 颜色支持定制

增强层: 螺旋钢丝 + 四层聚酯纤维编织布

Material structure:

Inner and outer tubes: blue industrial grade silicone, surface texture, color support customization

Reinforcing layer: spiral steel wire + four layers of polyester fiber woven cloth

尺寸规格:

内径: Ø6mm---102mm (支持定制)

标准长度: 6M

工作温度范围: -60°C / +180°C

Dimensions:

Internal diameter : Ø6mm---159mm

(Support customization)

Standard length : 6M

Length operating temperature range : -60°C / +180°C

产品应用:

该管柔软, 耐撕裂, 抗老化, 正常使用, 寿命极长。常被广泛用在风电行业中, 主要被用于风力网轮机系统中抽吸和输送防冻液等。

Product application:


The tube is soft, tear resistant, anti-aging, normal use, and extremely long service life. It is often widely used in the wind power industry, mainly used in the suction and delivery of anti Dongye in the wind turbine system.

Industrial silicone hose

品名	内径		壁厚 + _{-0.8} mm	工作压力		爆破压力		标准长度 米/根
	(mm)	(inch)		Bar	psi	Bar	psi	
SP60-006	6	1/4	4.5	26.0	377	78.0	1131	6
SP60-008	8	5/16	4.5	21.5	311.75	64.5	935.25	6
SP60-010	10	3/8	4.5	19.3	279.85	57.9	839.55	6
SP60-013	13	1/2	4.5	17.2	249.4	51.6	748.2	6
SP60-016	16	5/8	4.5	15.7	227.65	47.1	682.95	6
SP60-019	19	3/4	4.5	14.5	210.25	43.5	630.75	6
SP60-025	25	1	4.5	12.3	178.35	36.9	535.05	6
SP60-032	32	1-1/4	4.5	11.0	159.5	33.0	478.5	6
SP60-038	38	1-1/2	4.5	10.0	145	30.0	435	6
SP60-045	45	1-3/4	4.5	9.0	130.5	27.0	391.5	6
SP60-051	51	2	4.5	8.0	116	24.0	348	6
SP60-057	57	2-1/4	4.5	7.2	104.4	21.6	313.2	6
SP60-063	63	2-1/2	4.5	6.7	97.15	20.1	291.45	6
SP60-076	76	3	4.5	6.0	87	18.0	261	6
SP60-090	89	3-1/2	4.5	5.5	79.75	16.5	239.25	6
SP60-102	102	4	4.5	5.0	72.5	15.0	217.5	6

产品优势

Product advantages



适用流体类型

Applicable fluid type

