



抗静电橡胶编织软管 RE02

Antistatic rubber braided hose RE02



材料结构:

内/外管: 德国原装进口黑色耐高温、抗老化、防静电 EPDM 合成橡胶
增强层: 德国产高强度纤维增强层

Material structure:

Inner/outer pipe: black high temperature resistant, anti-aging, anti-static EPDM synthetic rubber imported from Germany with original packaging
Reinforcing layer: high-strength fiber reinforced layer made in Germany

产品应用:

适合化工行业等需防静电的场所, 常用来输送低压水蒸气、热水、弱酸碱、动植物油脂、酮、温和化学品。不可用于石油类介质。

Product application:

It is suitable for chemical industry and other places requiring anti-static. It is often used to transport low-pressure steam, hot water, weak acid and alkali, animal and vegetable oils, ketones, and mild chemicals. It cannot be used for petroleum media.

尺寸规格:

内径: Ø6mm---51mm (支持定制)
标准长度: 100M
工作温度范围: -40°C / +150°C

Dimensions:

Internal diameter : Ø6mm---51mm(Support customization)
Standard length : 100M
Length operating temperature range : -40°C / +150°C

产品优势

Product advantages



Industrial silicone hose

适用流体类型

Applicable fluid type



品名 product number	规格 specifications	内径I.D (mm)	外径O.D (mm)	工作压力 W.P (PSI)	爆破压力 B.P (PSI)	弯曲半径 Bend Radius (mm)	重量Weight (kg/m)	长度 Length m/piece
RE02-06	1/4"	6.4	13	300	1200	50	0.14	100
RE02-08	5/16"	7.9	15	300	1200	60	0.16	100
RE02-10	3/8"	9.5	17.0	300	1200	70	0.21	100
RE02-13	1/2"	12.7	21	300	1200	120	0.28	100
RE02-16	5/8"	15.9	24	300	1200	150	0.34	60
RE02-19	3/4"	19.0	28.0	300	1200	170	0.46	60
RE02-25	1"	25.4	36.0	200	800	200	0.7	60
RE02-32	1-1/4"	31.8	43.8	150	600	250	0.96	36
RE02-38	1-1/2"	38.1	51.0	150	600	300	1.2	30
RE02-41	1-5/8"	41.0	54.0	150	600	320	1.28	20
RE02-45	1-3/4"	45.0	58.0	150	600	350	1.48	20
RE02-50	2"	50.8	66.0	150	600	400	2	20