



防火多用途耐油橡胶管 RE03

Fireproof multipurpose oil resistant rubber tube RE03



适用流体类型

Applicable fluid type



产品应用:

MSHA 防火等级, RMA 等级耐油性, 超强耐候性。适用于恶劣的, 有防火要求的工业环境下输送燃气、油类、空气、水、乳化液等。用途广泛。注意该软管不导电, 耐电压 6000V 以上。

Product application:

MSHA fire rating, RMA grade oil resistance, and super weather resistance. It is suitable for conveying gas, oil, air, water, emulsion, etc. in harsh industrial environment with fire protection requirements. It is widely used. Note that the hose is non-conductive and has a withstand voltage of more than 6000V.

材料结构:

内管: RMA-A 高等级抗油性、气密性好的黑色 NBR 合成橡胶
增强层: 高强度纤维增强层
外管: 防火、耐油、耐磨抗老化 CSM 合成橡胶

Material structure:

Inner tube: RMA-A black NBR synthetic rubber with high oil resistance and good air tightness
Reinforcement layer: high-strength fiber reinforcement layer
Outer tube: fireproof, oil resistant, abrasion resistant and anti-aging CSM synthetic rubber

尺寸规格:

内径: Ø6mm---51mm (支持定制)
标准长度: 100M
工作温度范围: -30°C / +120°C


Dimensions:

Internal diameter : Ø6mm---51mm(Support customization)
Standard length : 100M
Length operating temperature range : -30°C / +120°C

Industrial silicone hose

产品优势

Product advantages



品名 product number	规格 specifications	内径I.D (mm)	外径O.D (mm)	工作压力 W.P (PSI)	爆破压力 B.P (PSI)	弯曲半径 Bend Radius (mm)	重量 Weight (kg/m)	长度 Length m/piece
RE03-06	1/4"	6.4	13	350	1400	50	0.15	100
RE03-08	5/16"	7.9	15	350	1400	60	0.18	100
RE03-10	3/8"	9.5	17	350	1400	70	0.23	100
RE03-13	1/2"	12.7	21	350	1400	120	0.31	100
RE03-16	5/8"	15.9	24	350	1400	150	0.38	60
RE03-19	3/4"	19	29	350	1400	170	0.58	60
RE03-25	1"	25.4	38	350	1400	200	0.88	60
RE03-32	1-1/4"	31.8	45	250	1000	250	1.2	36
RE03-38	1-1/2"	38.1	53	200	800	300	1.6	30
RE03-50	2"	50.8	68	200	800	400	2.4	20