



## 硅胶单鼓包直管 CAC20

Silica gel single drum wrapped straight pipe CAC20



### 材料结构：

内 / 外管：工业级硅胶，颜色支持定制  
增强层：三层或四层高强度涤纶编织布

### Material structure:

Inner /outer tubes: industrial grade silicone, color support customization  
Reinforcing layer: Three or four layers of high strength polyester woven cloth

### 尺寸规格：

内径：Ø38mm---102mm（支持定制）  
标准长度：76,90,100mm（支持定制）  
工作温度范围：-60°C / +180°C

### Dimensions:

Internal diameter : Ø38mm---102mm(Support customization)  
Standard length : 76,90,100mm(Support customization)  
Length operating temperature range : -60°C / +180°C

品名 (Reference) Part No.:	内径 (Inside Demesion)		壁厚 (Thickness) +/-0.3mm	布层 (Ply)	标准长度 (length) L1
	(mm)	(inch)			
CAC20-038	38	1.5"	4.5	三层涤纶	76mm
CAC20-051	51	2"	4.5	三层涤纶	76mm
CAC20-057	57	2.25"	4.5	三层涤纶	76mm
CAC20-063	63	2.5"	4.5	三层涤纶	76mm
CAC20-070	70	2.75"	4.5	三层涤纶	76mm
CAC20-076	76	3"	4.5	三层涤纶	76mm
CAC20-083	83	3.25"	4.5	三层涤纶	76mm
CAC20-089	89	3.5"	4.5	三层涤纶	76mm
CAC20-083	102	4"	5	四层涤纶	89mm

### 产品优势

### Product advantages



耐高低温



大口径



抗老化



支持定制



抗氧化



柔软

### 适用流体类型

### Applicable fluid type



油



水



气体



粉料

### 产品应用：

具有良好的耐温性和耐腐蚀性。可以过热空气和热水，主要应用汽车发动机，常用于各类车辆的发动机改装，赛车改装，也可用于各种机械设备中。也可做为汽车，货柜车，公共汽车发动机的冷却水管。

### Product application:

It has good temperature resistance and corrosion resistance. It can overheat air and hot water. It is mainly used in automobile engines. It is often used in engine refitting of various vehicles, car racing refitting, and also in various mechanical equipment. It can also be used as the cooling water pipe of automobile, container truck and bus engine.

**Automobile silicone hose**