

汽车减震软管 CAC30

Automobile damping hose CAC30



材料结构：

内管：有三种不同的内层结构，A 内层为一般耐高温硅胶。
 B 内层为具有良好耐油性氟硅胶。C 内层为具有耐溶剂的氟橡胶
 增强层：高强度纤维编织布 + 不锈钢圈
 外管：工业级硅胶，波纹状，颜色支持定制

Material structure:

Inner tube: there are three different inner structures.
 The inner layer of a is general high temperature resistant silica gel.
 B the inner layer is fluorosilicone with good oil resistance.
 C the inner layer is fluororubber with solvent resistance
 Reinforcing layer: high strength fiber woven cloth + stainless steel ring
 Outer tube: industrial grade silicone, corrugated, color support customization

尺寸规格：

内径：Ø51mm---102mm（支持定制）
 标准长度：200mm（支持定制）
 工作温度范围：-60°C / +180°C

Dimensions:

Internal diameter : Ø51mm---102mm(Support customization)
 Standard length : 200mm(Support customization)
 Length operating temperature range : -60°C / +180°C

适用流体类型

Applicable fluid type



产品应用：

具有良好的耐温和耐油性，专为汽车，卡车，货车，减震器用油管，内部采用氟硅胶，氟橡胶和一般硅胶三种，可用来作为抗油性能和减震性。推荐用于工业车辆的涡轮增压器系统。

Product application:

It has good temperature resistance and oil resistance. It is specially used for oil pipes for cars, trucks, trucks and shock absorbers. There are three kinds of internal fluorine silicone, fluorine rubber and general silicone, which can be used as oil resistance and shock absorption. Turbocharger system recommended for industrial vehicles.

Automobile silicone hose

产品优势

Product advantages



品名 Partname	内径 (ID)		壁厚 wall thick +1.0/-0.5mm	波纹 Waven PCS	钢圈 ring PCS	法兰长度 Flanglength mm	总长 Total length mm	工作压力 Working press		爆破压力 Burst Press	
	mm	inch						Bar	psi	Bar	psi
CAC30-051	51	2	4.5	4.0	5	43.5	200	8.0	116	24.0	348
CAC30-063	63	2-1/2	4.5	4.0	5	43.5	200	7.0	101.5	21.0	304.5
CAC30-076	76	3	4.5	4.0	5	43.5	200	6.0	87	18.0	261
CAC30-090	90	3-1/2	4.5	4.0	5	48.5	210	5.0	72.5	15.0	217.5
CAC30-102	102	4	4.5	4.0	5	48.5	210	4.0	58	12.0	174