



柴油 DEF 尿素溶液专用输送橡胶软管

Special delivery rubber hose for diesel DEF urea solution



材料结构：

内 / 外管：黑色超耐磨，抗老化，防静电，耐车用尿素溶液合成橡胶

增强层：高强度合成纤维编织层

Material structure:

Inner/outer tube: black, super wear-resistant, anti-aging, anti-static, and resistant to synthetic rubber of urea solution for vehicles

Reinforcing layer: high-strength synthetic fiber woven layer

尺寸规格：

内径：Ø19mm---51mm（支持定制）

标准长度：60M

工作温度范围：-40°C / +90°C

Dimensions:

Internal diameter : Ø19mm---51mm(Support customization)

Standard length : 60M

Length operating temperature range : -40°C / +90°C

适用流体类型

Applicable fluid type



油



水



气体

产品优势

Product advantages



抗静电



抗高压



耐低温



车用尿素专用



支持定制



抗氧化



弯曲性好



耐磨

产品应用：

对车用尿素溶液有很好的适用性，常用于车辆 SCR 系统，符合 SAE J2902-2013 标准，能有效保护车辆 SCR 系统，帮助柴油车辆满足排放法规。内外塑双防静电，也适用于加油站等需要反复缠绕、滚动摩擦，对静电有要求的场景。

Product application:

Vehicle SCR system components comply with SAE J2902-2013 standard to protect vehicle SCR system and help diesel vehicles meet emission regulations. Internal and external plastic double anti-static, gas station and other places requiring repeated winding and rolling friction are very suitable

Industrial silicone hose

品名 product number	内径I.D		外径O.D (mm)	工作压力 W.P (bar)	爆破压力 (bar)	弯曲半径 Bend Radius (mm)	重量Weight (kg/m)	长度 Length m/piece
	(mm)	(inch)						
DEF019	19	3/4"	28	14	56	120	0.42	60
DEF022	22.2	7/8"	32.2	14	56	190	0.55	60
DEF025	25.4	1"	37	14	56	200	0.72	60
DEF032	31.8	1-1/4"	46	10	40	250	1.1	36
DEF038	38.1	1-1/2"	53	10	40	300	1.37	30
DEF051	50.8	2"	68	10	40	400	2.06	20